

PANTUM

The New Era for Printing

P3300 Series Monochrome Laser Printer

Reduce your printing cost at utmost

Let the new Pantum P3300 series bring your business value with auto-duplex high speed printing for high working efficiency, low paper jam rate for fluent operation, and eco-friendly separate drum unit and toner cartridge to reduce your cost at utmost. It is ideally suited for users no matter from small business group or from large shared workgroup who require affordable running cost.



Silent printing mode to lower the noise and create a comfortable office environment



Wifi One Step Installation and Direct Printing



Office document direct print from mobile devices



Low paper jam rate design for engine



High print speed



Convenient to print



Separate drum and toner



PANTUM

WWW.PANTUM.COM

KEY SPECIFICATIONS



P3300 Series Monochrome Laser Printer

Model	P3300DN		:	P3300DW	
Printing					
Print technology		Mono laser			
Print speed		33ppm(A4)/35ppm(Letter)			
First print out time		Less than 8.2 seconds			
Max. monthly volume		60000 pages			
Recommended monthly volume		750 to 3500 pages			
Processor speed		350 MHz			
Memory		256 MB			
Resolution(dpi)		1200x1200 dpi (Max)			
Printer language		PCL5e, PCL6, PS3, PDF			
Duplex mode		Auto			
Control panel		2Line LCD			
NFC print	No	:	:	:	Yes
Network print		:	:	:	Yes
Wireless print	No	:	:	:	Yes
Paper handling					
Paper input tray		250 pages			
Multipurpose tray		1 pages			
Paper output tray		150 pages			
Media types		Plain,Thick,Transparency,Cardstock,Lable,Envelope			
Media sizes		A4, A5, JIS B5 ,ISO B5 , A6, Letter, Legal,Executive, Folio, Oficio, Statement, Japanese Postcard, Monarch Env, DL Env, C5 Env, C6 Env, No.10 Env, ZL, Big 16K, Big 32K, 16K, 32K, B6, Yougata4, Postcard, Younaga3, Nagagata3, Yougata2			
Media weight		Input tray: 60-105g/m² Multipurpose tray: 60-200g/m²			
General					
Dimensions (wxdxh)		354 x334x 232mm(13.9x 13.1x9.1in)			
Weight (without toner cartridge)		6.8kg (15lb)			
Operating temperature range		10-32℃ (50-95°F)			
Operating humidity range		20% - 80% RH			
Input voltage		110V Model:AC100-127V(±10%), 50/60Hz(±2Hz), 9A 220V Model: AC220-240V(-15%,+10%), 50/60Hz(±2Hz), 4.5A			
Noise		Printing: ≦52dB(A) Standby: ≦30dB(A)			
Power consumption		Print:Average 525W Standby:50W Dormant:Less than 2 W			
Operating system compatibility		Windows Server2003/2008/2012/ XP/ Vista/Win 7/Win 8/Win8.1/ Win10; Mac OS 10.7~10.13; Linux (ubuntu12.04/14.04);	:	Windows Server2003/2008/2012/ XP/ Vista/Win 7/Win 8/Win8.1/ Win10; Mac OS 10.7~10.13; Linux (ubuntu12.04/14.04); iOS 7.0 and above; Android 4.4 and above	
Interface		High-speedUSB2.0 Ethernet: IEEE 802.3 10/100Base-Tx	:	High-speedUSB2.0 Ethernet: IEEE 802.3 10/100Base-Tx Wifi: IEEE 802.11b/g/n	
Supplies					
Cartridge style		Separate drum and toner			
Starter cartridge capacity ⁽¹⁾		TL-410 (1500 pages)			
Cartridge and drum capacity ⁽¹⁾		Cartridge:TL-410 (1500 pages, Standard); TL-410H (3000 pages, High); TL- 410X (6000 pages ,Extra high) Drum:DL-410 (12000pages)			
Starter drum unit lifetime ⁽¹⁾ (Print with A4 paper page by page discontinuously)		DL-410 (12000 pages)			
What s in the box					

(1) Average yield per toner cartridge in accordance with ISO/IEC 19752 (Individual users will experience different results based on their environment and page coverage)

Copyright ©2017 Pantum International Limited. The information contained herein is subject to change without notice. Pantum shall not be liable for technical or editorial errors or omissions contained herein.